



MJ N-Channel Enhancement Mode Power MOSFET

Description

The MJ3018AS uses advanced trench technology and design to provide excellent $R_{DS(ON)}$ with low gate charge. It can be used in a wide variety of applications.

General Features

- VDS =30V,ID =18A
 RDS(ON) <7mΩ @ VGS=10V
 RDS(ON) <10mΩ @ VGS=4.5V
- High density cell design for ultra low Rdson
- Fully characterized avalanche voltage and current

Application

- Power switching application
- Hard Switched and High Frequency Circuits
- Uninterruptible Power Supply



Schematic diagram



Marking and pin Assignment



SOP-8 top view

Package Marking and Ordering Information

Device Marking	Device	Device Package	Reel Size	Tape width	Quantity
MJ3018AS	MJ3018AS	SOP-8	Ø330mm	12mm	4000 units

Absolute Maximum Ratings (T_A=25℃ unless otherwise noted)

Parameter	Symbol	Limit	Unit
Drain-Source Voltage	Vds	30	V
Gate-Source Voltage	Vgs	±20	V
Drain Current-Continuous	lo	18	А
Drain Current-Continuous(T _A =100°C)	ID(100℃)	12.7	А
Pulsed Drain Current	Ідм	72	А
Maximum Power Dissipation	PD	3	W
Single pulse avalanche energy (Note 5)	Eas	204	mJ
Operating Junction and Storage Temperature Range	Тл,Тята	-55 To 150	°C

Thermal Characteristic

Thermal Resistance, Junction-to-Ambient (Note 2) Reja	42	°C/W
---	----	------





Electrical Characteristics (T_A=25℃ unless otherwise noted)

Parameter	Symbol	Condition	Min	Тур	Max	Unit
Off Characteristics						
Drain-Source Breakdown Voltage	BVDSS	V _{GS} =0V,I _D =250µA	30	33	-	V
Zero Gate Voltage Drain Current	loss	Vds=30V,Vgs=0V	-	-	1	μA
Gate-Body Leakage Current	lgss	VDS=±20V,VDS=0V	-	-	±100	nA
On Characteristics (Note 3)						
Gate Threshold Voltage	$V_{GS(th)}$	V⊳s=V₀s ,I⊳=250µA	0.7	1.1	1.4	V
Drain Source On State Registence		Vgs=10V, Id=12A	-	5.5	7	mΩ
	RDS(ON)	Vgs=4.5V, Id=10A	-	6.5	10	mΩ
Forward Transconductance	g fs	VDs=5V,ID=12A	5	-	-	S
Dynamic Characteristics (Note 4)		-				
Input Capacitance	Clss	V _{DS} =15V,V _{GS} =0V F=1.0MHz	-	2100	-	PF
Output Capacitance	Coss		-	460	-	PF
Reverse Transfer Capacitance	Crss		-	230	-	PF
Switching Characteristics (Note 4)						
Turn-on Delay Time	td(on)	Vdd=5V,Id=12A Vgs=10V,Rgen=2.7Ω	-	20	-	nS
Turn-on Rise Time	tr		-	15	-	nS
Turn-Off Delay Time	td(off)		-	60	-	nS
Turn-Off Fall Time	tr		-	10	-	nS
Total Gate Charge	Qg		-	41	-	nC
Gate-Source Charge	Qgs	V _{DS} =15V,I _D =12A V _{GS} =10V	-	14	-	nC
Gate-Drain Charge	Qgd		-	11	-	nC
Drain-Source Diode Characteristics						
Diode Forward Voltage (Note 3)	Vsd	V _{GS} =0V,I _S =18A	-	-	1.2	V
Diode Forward Current (Note 2)	ls		-	-	18	А

Notes:

① Repetitive Rating: Pulse width limited by maximum junction temperature.

② Surface Mounted on FR4 Board, $t \leq 10$ sec.

③ Pulse Test: Pulse Width \leq 300µs, Duty Cycle \leq 2%.

④ Guaranteed by design, not subject to production

(5) EAS condition: Tj=25°C,V_DD=15V,V_G=10V,L=0.5mH,Rg=25 Ω







Test circuit







Gate charge test Circuit



Switch Time Test Circuit







Typical Electrical and Thermal Characteristics (Curves)



Figure 3 Rdson- Drain Current

Figure 6 Source- Drain Diode Forward









Square Wave Pluse Duration(sec) Figure 11 Normalized Maximum Transient Thermal Impedance





SOP-8 Package Information



COMMON DIMENSIONS (UNITS OF MEASURE=MILLIMETER)

SYMBOL	MIN	NOM	MAX	
A	1.35	1.55	1.75	
A1	0.10	0.15	0.25	
A2	1.25	1.40	1.65	
A3	0.50	0.60	0.70	
b	0.38	-	0.51	
b1	0.37	0.42	0.47	
с	0.18	-	0.25	
c1	0.17	0.20	0.23	
D	4.80	4.90	5.00	
E	5.80	6.00	6.20	
E1	3.80	3.90	4.00	
е	1.17	1.27	1.37	
L	0.45	0.60	0.80	
L1	1.04REF			
L2	0.25BSC			
R	0.07	—	I	
R1	0.07	—	-	
h	0.30	0.40	0.50	
θ	0.	-	8'	
θ 1	15*	17	19*	
θ2	11*	13	15*	
θ3	15*	17	19*	
θ4	11*	13°	15*	





Attention:

Any and all MJ power products described or contained herein do not have specifications that can handle applications that require extremely high levels of reliability, such as life-support systems, aircraft's control systems, or other applications whose failure can be reasonably expected to result in serious physical and/or material damage. Consult with your MJ power representative nearest you before using any MJ power products described or contained herein in such applications.

MJ power assumes no responsibility for equipment failures that result from using products at values that exceed, even momentarily, rated values (such as maximum ratings, operating condition ranges, or other parameters) listed in products specifications of any and all MJ power products described or contained herein.

Specifications of any and all MJ power products described or contained herein stipulate the erformance, characteristics, and functions of the described products in the independent state, and are not guarantees of the performance, characteristics, and functions of the described products as mounted in the customer's products or equipment. To verify symptoms and states that cannot be evaluated in an independent device, the customer should always evaluate and test devices mounted in the customer's products or equipment.

MJ power Semiconductor CO.,LTD. strives to supply high-quality high-reliability products. However, any and all semiconductor products fail with some probability. It is possible that these probabilistic failures could give rise to accidents or events that could endanger human lives, that could give rise to smoke or fire, or that could cause damage to other property. When designing equipment, adopt safety measures so that these kinds of accidents or events cannot occur. Such measures include but are not limited to protective circuits and error prevention circuits for safe design, redundant design, and structural design.

In the event that any or all MJ power products (including technical data, services) described or contained herein are controlled under any of applicable local export control laws and regulations, such products must not be exported without obtaining the export license from the authorities concerned in accordance with the above law.

No part of this publication may be reproduced or transmitted in any form or by any means, electronic or mechanical, including photocopying and recording, or any information storage or retrieval system, or therwise, without the prior written permission of MJ power Semiconductor CO.,LTD.

Information (including circuit diagrams and circuit parameters) herein is for example only; it is not guaranteed for volume production. MJ power believes information herein is accurate and reliable, but no guarantees are made or implied regarding its use or any infringements of intellectual property rights or other rights of third parties.

Any and all information described or contained herein are subject to change without notice due to product/technology improvement, etc. When designing equipment, refer to the "Delivery Specification" for the MJ power product that you intend to use.

This catalog provides information as of Sep.2010. Specifications and information herein are subject to change without notice.