

N-Channel Super Junction Power MOSFET III

General Description


The series of devices use advanced super junction technology and design to provide excellent $R_{DS(ON)}$ with low gate charge. This super junction MOSFET fits the industry's AC-DC SMPS requirements for PFC, AC/DC power conversion, and industrial power applications.

Features

- ◆ New technology for high voltage device
- ◆ Low on-resistance and low conduction losses
- ◆ Small package
- ◆ Ultra Low Gate Charge cause lower driving requirements
- ◆ 100% Avalanche Tested
- ◆ ROHS compliant



Schematic diagram



TO-247

Application

- ◆ Power factor correction (PFC)
- ◆ Switched mode power supplies(SMPS)
- ◆ Uninterruptible Power Supply (UPS)

V_{DS}	650	V
$R_{DS(ON)TYP}$	36	m Ω
I_D	75	A

Package Marking And Ordering Information

Device	Device Package	Marking
MJ65TF041T	TO-247	MJ65TF041T

Table 1. Absolute Maximum Ratings (Tc=25°C)

Parameter	Symbol	Value	Unit
Drain-Source Voltage ($V_{GS}=0V$)	V_{DS}	650	V
Gate-Source Voltage ($V_{DS}=0V$) AC ($f>1$ Hz)	V_{GS}	± 30	V
Continuous Drain Current at $T_c=25^{\circ}C$	I_D (DC)	75	A
Continuous Drain Current at $T_c=100^{\circ}C$	I_D (DC)	47	A
Pulsed drain current ^(Note 1)	I_{DM} (pluse)	300	A
Maximum Power Dissipation ($T_c=25^{\circ}C$)	P_D	510	W
Derate above 25°C	P_D	4.08	W/°C
Single pulse avalanche energy ^(Note 2)	E_{AS}	1936	mJ
Avalanche current ^(Note 1)	I_{AR}	28	A
Repetitive Avalanche energy, t_{AR} limited by T_{jmax} ^(Note 1)	E_{AR}	2.5	mJ

Parameter	Symbol	Value	Unit
Drain Source voltage slope, $V_{DS} \leq 480$ V	dv/dt	50	V/ns
Reverse diode dv/dt, $V_{DS} \leq 480$ V, $I_{SD} < I_D$	dv/dt	50	V/ns
Operating Junction and Storage Temperature Range	T_J, T_{STG}	-55...+150	°C

* limited by maximum junction temperature

Table 2. Thermal Characteristic

Parameter	Symbol	Value	Unit
Thermal Resistance, Junction-to-Case (Maximum)	R _{thJC}	0.245	°C/W
Thermal Resistance, Junction-to-Ambient (Maximum)	R _{thJA}	62	°C/W

Table 3. Electrical Characteristics (T_A=25°C unless otherwise noted)

Parameter	Symbol	Condition	Min	Typ	Max	Unit
On/off states						
Drain-Source Breakdown Voltage	BV _{DSS}	V _{GS} =0V I _D =500μA	650	-	-	V
Zero Gate Voltage Drain Current (Tc=25°C)	I _{DSS}	V _{DS} =650V,V _{GS} =0V	-	-	5	μA
Zero Gate Voltage Drain Current (Tc=125°C)	I _{DSS}	V _{DS} =650V,V _{GS} =0V	-	-	500	μA
Gate-Body Leakage Current	I _{GSS}	V _{GS} =±20V,V _{DS} =0V	-	-	±100	nA
Gate Threshold Voltage	V _{GS(th)}	V _{DS} =V _{GS} ,I _D =500μA	2.5	3.5	4.5	V
Drain-Source On-State Resistance	R _{DS(ON)}	V _{GS} =10V,I _D =38A	-	36	41	mΩ
Dynamic Characteristics						
Input Capacitance	C _{ies}	V _{DS} =100V,V _{GS} =0V F=1.0MHz	-	7300	8500	PF
Output Capacitance	C _{OSS}		-	252	-	PF
Reverse Transfer Capacitance	C _{rss}		-	4	-	PF
Total Gate Charge	Q _g	V _{DS} =480V,I _D =75A V _{GS} =10V	-	116	135	nC
Gate-Source Charge	Q _{gs}		-	40	-	nC
Gate-Drain Charge	Q _{gd}		-	30	-	nC
Switching times						
Turn-on Delay Time	t _{d(on)}	V _{DD} =380V,I _D =38A R _G =1.2Ω,V _{GS} =10V	-	27	-	nS
Turn-on Rise Time	t _r		-	22	-	nS
Turn-Off Delay Time	t _{d(off)}		-	118	180	nS
Turn-Off Fall Time	t _f		-	13	30	nS
Source- Drain Diode Characteristics						
Source-drain current (Body Diode)	I _{SD}	T _C =25°C	-	75	-	A
Pulsed Source-drain current (Body Diode)	I _{SDM}		-	300	-	A
Forward On Voltage	V _{SD}	T _J =25°C,I _{SD} =75A,V _{GS} =0V	-	1.3	-	V
Reverse Recovery Time	t _{rr}	T _J =25°C,I _F =38A di/dt=100A/μs,V _{DD} =300V	-	230	-	nS
Reverse Recovery Charge	Q _{rr}		-	3	-	uC
Peak reverse recovery Current	I _{rrm}		-	26	-	A

Notes

- 1.Repetitive Rating: Pulse width limited by maximum junction temperature
2. $T_J=25^{\circ}\text{C}$, $V_{DD}=50\text{V}$, $V_G=10\text{V}$, $R_G=25\Omega$

TYPICAL ELECTRICAL AND THERMAL CHARACTERISTICS (curves)




Figure 1 Safe operating area




Figure 2 Source-Drain Diode Forward Voltage




Figure 3 Output characteristics




Figure 4 Transfer characteristics




Figure 5 Static drain-source on resistance




Figure 6 $R_{DS(ON)}$ vs Junction Temperature




Figure 7 BV_{DSS} vs Junction Temperature





Figure 8 Maximum I_D vs Junction Temperature



Test circuit



Gate charge test circuit & Waveform




Switch Time Test Circuit



Unclamped Inductive Switching Test Circuit & Waveforms

TO-247 Package Information



Symbol	Dimensions In Millimeters		Dimensions In Inches	
	Min.	Max.	Min.	Max.
A	4.850	5.150	0.191	0.200
A1	2.200	2.600	0.087	0.102
b	1.000	1.400	0.039	0.055
b1	2.800	3.200	0.110	0.126
b2	1.800	2.200	0.071	0.087
c	0.500	0.700	0.020	0.028
c1	1.900	2.100	0.075	0.083
D	15.450	15.750	0.608	0.620
E1	3.500 REF		0.138 REF	
E2	3.600 REF		0.142 REF	
L	40.900	41.300	1.610	1.626
L1	24.800	25.100	0.976	0.988
L2	20.300	20.600	0.799	0.811
Φ	7.100	7.300	0.280	0.287
e	5.450 TYP		0.215 TYP	
H	5.980 REF		0.235 REF	

Attention:

Any and all MJ power products described or contained herein do not have specifications that can handle applications that require extremely high levels of reliability, such as life-support systems, aircraft's control systems, or other applications whose failure can be reasonably expected to result in serious physical and/or material damage. Consult with your MJ power representative nearest you before using any MJ power products described or contained herein in such applications.

MJ power assumes no responsibility for equipment failures that result from using products at values that exceed, even momentarily, rated values (such as maximum ratings, operating condition ranges, or other parameters) listed in products specifications of any and all MJ power products described or contained herein.

Specifications of any and all MJ power products described or contained herein stipulate the performance, characteristics, and functions of the described products in the independent state, and are not guarantees of the performance, characteristics, and functions of the described products as mounted in the customer's products or equipment. To verify symptoms and states that cannot be evaluated in an independent device, the customer should always evaluate and test devices mounted in the customer's products or equipment.

MJ power Semiconductor CO.,LTD. strives to supply high-quality high-reliability products. However, any and all semiconductor products fail with some probability. It is possible that these probabilistic failures could give rise to accidents or events that could endanger human lives, that could give rise to smoke or fire, or that could cause damage to other property. When designing equipment, adopt safety measures so that these kinds of accidents or events cannot occur. Such measures include but are not limited to protective circuits and error prevention circuits for safe design, redundant design, and structural design.

In the event that any or all MJ power products(including technical data, services) described or contained herein are controlled under any of applicable local export control laws and regulations, such products must not be exported without obtaining the export license from the authorities concerned in accordance with the above law.

No part of this publication may be reproduced or transmitted in any form or by any means, electronic or mechanical, including photocopying and recording, or any information storage or retrieval system, or otherwise, without the prior written permission of MJ power Semiconductor CO.,LTD.

Information (including circuit diagrams and circuit parameters) herein is for example only ; it is not guaranteed for volume production. MJ power believes information herein is accurate and reliable, but no guarantees are made or implied regarding its use or any infringements of intellectual property rights or other rights of third parties.

Any and all information described or contained herein are subject to change without notice due to product/technology improvement, etc. When designing equipment, refer to the "Delivery Specification" for the MJ power product that you intend to use.

This catalog provides information as of Sep.2010. Specifications and information herein are subject to change without notice.